

Product Introduction

- 1、 High power LED underground light, fashionable and beautiful appearance. The light body uses the design of increasing heat dissipation space, the buried barrel adopts aluminium alloy compression moulding forming. Surface with anodizing treatment has the stronger structure and anti-corrosion capability, that its thermal conductivity is 200 times higher than the normal project plastic's, meet the LED light body requirement for heat conduct to the outside of concrete and land, fully ensure the stability and long lifespan of LED fixture.
- 2、 Stainless steel faceplate, high pressure die casting light body, surface with electrostatic plastic coating. Lampshade adopts high strength toughened glass, resist the impact and friction.
- 3、 Adopt American CREE original LED light source, high flus output, excellent consistency of light color; Constant current driver with PWM gray control installed inside, RGB gray level reaches to 65,536 degree equally, make the light result much beautiful.
- 4、 Powerful DMX512 interface adopts high reliable bus connect, all has the function of automatic addressing.

Specification




Product Code	2150CE-12	2150CD-12	2150CC-24	2150CB-24	2150CF-12
LED Brand	CREE	CREE	CREE	CREE	CREE RGBW 4 in 1
LED Quantity	12pcs	12pcs	24pcs	24pcs	12pcs
Rated Power	60W	42W	60W	42W	100W
Input Voltage	AC100-240V	AC100-240V	DC24V/AC100-240V	DC24V/AC100-240V	DC24V/AC100-240V
Frequency Range	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Color	Single	Single	RGB/Single	RGB/Single	RGBW
Beam Angle	3.5° 8° 12° 20° 30° 60° 10x70°		5° 12.5° 20° 30° 45°	60° 15X30° 10X60°	15° 20° 30° 15x60°
Control Mode	CC	CC	DMX512/CC	DMX512/CC	DMX512
Life	50000H	50000H	50000H	50000H	50000H
Protection Grade	IP67	IP67	IP67	IP67	IP67
Ambient Temperature	- 25°C ~ 50°C	- 25°C ~ 50°C	- 25°C ~ 50°C	- 25°C ~ 50°C	- 25°C ~ 50°C
Ambient Humidity	10% ~ 90%°	10% ~ 90%°	10% ~ 90%	10% ~ 90%	10% ~ 90%



Inground Light Series

2150C





www.cadprojects.in