

# Flood Light Series

SL1126F



1126S



www.elects.in

## Specification

| Product Code            | 1126FB-3                    | 1126FA-3      | 1126F-C6    |
|-------------------------|-----------------------------|---------------|-------------|
| LED品牌LED Brand          | CREE                        | CREE          | CREE COB    |
| LED数量LED Quantity       | 3pcs                        | 3pcs          | 1pc         |
| 额定功率Rated Power         | 6W                          | 3.5W          | 6W          |
| 输入电压Input Voltage       | AC100-240V                  | AC100-240V    | AC100-240V  |
| 频率Frequency Range       | 50/60Hz                     | 50/60Hz       | 50/60Hz     |
| 颜色Color                 | Single                      | Single        | Single      |
| 发光角度Beam Angle          | 5° 8° 12.5° 20° 30° 45° 60° | 15X30° 10X60° | 20°         |
| 控制方式Control Mode        | CC                          | CC            | CC          |
| 使用寿命Life                | 50000H                      | 50000H        | 50000H      |
| 防护等级Protection Grade    | IP66                        | IP66          | IP66        |
| 环境温度Ambient Temperature | - 25℃ ~ 50℃                 | - 25℃ ~ 50℃   | - 25℃ ~ 50℃ |
| 环境湿度Ambient Humidity    | 10% ~ 90%                   | 10% ~ 90%     | 10% ~ 90%   |

## Specification

| Product Code        | 1126SB-3                    | 1126SA-3      | 1126S-C6      |
|---------------------|-----------------------------|---------------|---------------|
| LED Brand           | CREE                        | CREE          | CREE COB      |
| LED Quantity        | 3pcs                        | 3pcs          | 1pc           |
| Rated Power         | 6W                          | 3.5W          | 6W            |
| Input Voltage       | AC100-240V                  | AC100-240V    | AC100-240V    |
| Frequency Range     | 50/60Hz                     | 50/60Hz       | 50/60Hz       |
| Color               | Single                      | Single        | Single        |
| Beam Angle          | 5° 8° 12.5° 20° 30° 45° 60° | 15X30° 10X60° | 20°           |
| Control Mode        | CC                          | CC            | CC            |
| Life                | 50000H                      | 50000H        | 50000H        |
| Protection Grade    | IP66                        | IP66          | IP66          |
| Ambient Temperature | - 25°C ~ 50°C               | - 25°C ~ 50°C | - 25°C ~ 50°C |
| Ambient Humidity    | 10% ~ 90%                   | 10% ~ 90%     | 10% ~ 90%     |



