Product Introduction

- Recessed in-ground liner LED wall washer, fashion and beautiful appearance; with the design of increasing heat dissipation to fully ensure the stability and long lifespan of LED fixture.
- 2. Adjustable beam angle illuminant module make the effect of washing wall accurate and perfect.
- 3. The light body adopts #6063 aluminum alloy molding, surface with anodizing treatment; Faceplate use stainless steel; Lampshade adopts high strength toughened glass, resist the impact and friction. and use aluminum alloy buried barrel.
- 4. Adopt American CREE original LED light source, high flus output, excellent consistency of light color; Constant current driver with PWM gray control installed inside, RGB gray level reaches to 65,536 degree equally, make the light result much beautiful.
- 5. Powerful DMX512 interface adopts high reliable bus connect, all has the function of automatic addressing.

Specification

Product Code	2306A-36	2306A-24	2306A-18	2306A-9(0.5m)	2306A-6(0.3m)	2306-48
LED Brand	CREE	CREE	CREE	CREE	CREE	EPISTAR
LED Quantity	36pcs	24pcs	18pcs	9pcs	6pcs	48pcs
'Rated Power	42W	28W	21W	11W	7W	11W
Input Voltage	DC24V/AC100-240V	DC36V/AC100-240V	DC24V/AC100-240V	DC24V/AC100-240V	DC24V/AC100-240V	DC24V/AC100-240V
Frequency Range	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Color	RGB/Single	RGB/Single	RGB/Single	RGB/Single	RGB/Single	RGB/Single
Beam Angle	5° 8° 12.5° 20° 30° 45° 60° 15X30° 10X60°					>120°
'Control Mode	DMX512/CC	DMX512/CC	DMX512/CC	DMX512/CC	DMX512/CC	DMX512/CC
Life	30000H	30000H	30000H	30000H	50000H	50000H
Protection Grade	IP67	IP67	IP67	IP67	IP67	IP67
Ambient Temperature	-25℃~50℃	-25℃~50℃	-25℃~50℃	- 25℃ ~ 50℃	- 25°C ~ 50°C	- 25°C ~ 50°C
Ambient Humidity	10% ~ 90%	10% ~ 90%	10% ~ 90%	10% ~ 90%	10% ~ 90%	10% ~ 90%
Product Code	2306H-24					15
LED Brand	CREE RGBW 4 in1			•		
LED Quantity	24pcs			0		
Rated Power	48W			N ₀		
Input Voltage	DC24V			0.4		
Frequency Range	1			9/6		
Color	RGBW			201		
Beam Angle	20° 40° 60° 15X6	0°				
Control Mode	DMX512					
'Life	30000H					
Protection Grade	IP67					
Ambient Temperature	-25℃~50℃					
Ambient Humidity	10% ~ 90%					



Inground Light Series 2306



Stainless Steel Panel







